



## TECHNICAL DATA SHEET - PLOTTER VINYLs - POLYPROPYLENE TAPE HEX 930 MEDIUM TACK

A 100- $\mu$ m, transparent PP film, which is coated with a pressure-sensitive rubber adhesive. Intended for creating and applying kits (logos, cut letters ideally between 5 cm and 31 cm (1.97 in. and 12.20 in.) etc.).

### **FILM FEATURES:**

	<u>Indicative values</u>
• Thickness of film + adhesive ( $\mu$ m):	100
• Tensile strength (N/25mm):	66
• Elongation at break (%):	> 100

### **ADHESIVE PROPERTIES:**

	<u>Indicative value</u>
• Peel strength test 90° on steel (N/25mm):	1.9

### **ADHESIVE:**

- Natural rubber latex.

### **USER'S INSTRUCTIONS:**

- Dry application recommended.
- Recommended minimum application temperature: +15 °C (+59 °F)
- Operating temperature range: from +15 °C to +35 °C (+59 °F to +95 °F).
- Tape for use with high-precision applications, superimposed applications, and applications of coloured films whether they are calendered or cast.
- Good adhesion to the liner, high transparency and reduced tunnelling.

### **STORAGE:**

- Shelf life (before application):

The shelf life of this film is 6 months when stored unopened in its original packaging at a temperature ranging from +15 °C to +25 °C (+59 °F to +77 °F) with relative humidity between 30 % and 70 %.

### **NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).